


MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product Name 856 – FA003C Pro Link Baseboard Stripper
CAS # Mixture
Product Use Stripper
Manufacturer Pro-Link, Inc.
Ottawa, ON K1Z 1E9
Canada
Phone: 1-800-74-LINKS
Emergency Phone: 1-866-836-8855

LEGEND HMIS/NFPA	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

Health	/ 2
Flammability	2
Physical Hazard	0
Personal Protection	B



2. Hazards Identification

Emergency Overview DANGER -- CORROSIVE
Toxic. May be fatal if swallowed or inhaled.
May cause sensitisation by skin contact.
Contents under pressure. Containers may explode when heated.

Potential short term health effects

Routes of exposure Eye, Skin contact, Skin absorption, Inhalation, Ingestion.
Eyes Causes chemical burns. May cause blindness.
Skin May cause chemical burns. Harmful contact may not cause immediate pain. Contains a potential skin sensitizer. This product may be harmful if it is absorbed through the skin.

NIOSH - Pocket Guide - Skin Notations

Ethylene glycol monobutyl ether 111-76-2 Potential for dermal absorption

Inhalation Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness).

Ingestion Not a normal route of exposure. May cause stomach distress, nausea or vomiting.

Target organs Blood. Eyes. Kidney. Liver. Respiratory system. Skin.

Chronic effects Prolonged or repeated exposure can cause drying, defatting and dermatitis.

Signs and symptoms The product causes burns of eyes, skin and mucous membranes. Symptoms are prostration, gasping, pallor, and uncoordinated movements. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

3. Composition/Information on Ingredients

Ingredient(s)	CAS #	Percent
Propane	74-98-6	1 - 5
Pine oil	8002-09-3	1 - 5
Ethylene glycol monobutyl ether	111-76-2	15 - 40
Butane	106-97-8	3 - 7

4. First Aid Measures

First aid procedures

Eye contact Immediately flush with cool water. Remove contact lenses, if applicable, and continue flushing for 15 minutes. Obtain medical attention immediately.

Skin contact	Immediately flush with water. Wash with soap and water. Obtain medical attention if irritation persists.
Inhalation	If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. If breathing has stopped, trained personnel should administer CPR immediately.
Ingestion	Do not induce vomiting. Rinse mouth with water, then drink one or two glasses of water. Obtain medical attention. Never give anything by mouth if victim is unconscious, or is convulsing.
Notes to physician	Symptoms may be delayed.
General advice	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children. Immediate medical attention is required.

5. Fire-fighting Measures

Flammable properties	Not flammable by WHMIS criteria. Containers may explode when heated.
Extinguishing media	
Suitable extinguishing media	Carbon dioxide. Alcohol foam. Dry chemical.
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Protection of firefighters	
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. Cool containers with flooding quantities of water until well after fire is out.
Protective equipment for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.
Explosion data	
Sensitivity to mechanical impact	Not available
Sensitivity to static discharge	Not available

6. Accidental Release Measures

Personal precautions	Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Before attempting clean up, refer to hazard data given above. Remove sources of ignition. Although the chance of a significant spill or leak is unlikely in aerosol containers, in the event of such an occurrence, absorb spilled material with a non-flammable absorbent such as sand or vermiculite.

7. Handling and Storage

Handling	Use good industrial hygiene practices in handling this material. Do not get this material in your eyes, on your skin, or on your clothing.
Storage	Keep out of reach of children. Do not store at temperatures above 49°C (120.2°F). Keep away from heat, open flames or other sources of ignition.

8. Exposure Controls / Personal Protection

Exposure limits

Ingredient(s)	Exposure limits
Butane	ACGIH-TLV TWA: 1000 ppm
Ethylene glycol monobutyl ether	ACGIH-TLV TWA: 20 ppm
Pine oil	ACGIH-TLV Mist: 5 mg/m ³
Propane	ACGIH-TLV TWA: 1000 ppm

Engineering controls

General ventilation normally adequate. Provide adequate ventilation.

Personal protective equipment

Eye/Face protection

Wear chemical goggles.

Hand protection

Rubber gloves. Confirm with a reputable supplier first.

Skin and body protection

As required by employer code.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Avoid breathing mists or vapours.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. Wash hands and face before breaks and immediately after handling the product.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas
Colour	Brown - Tan
Form	Spray
Odour	Solvent
Odour threshold	Not available
Physical state	Gas
pH	12.2
Freezing point	Not available
Boiling point	124.00 °C (255.2 °F)
Flash point	< -17.77 °C (< 0 °F) (Propellant)
Evaporation Rate	Not available
Flammability	12.62 kJ/g
Flammability limits in air, lower, % by volume	Not available
Flammability Limits in Air, Upper, % by Volume	Not available
Vapour pressure	377 kPa
Vapour density	Not available
Specific gravity	0.984 (Concentrate)
Octanol/water coefficient	Not available
Solubility (H ₂ O)	Partially soluble
Auto-ignition temperature	Not available
VOC (Weight %)	Not available
Viscosity	Not available
Percent volatile	Not available

10. Chemical Stability & Reactivity Information

Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Reacts violently with acids. This product may react with oxidizing agents. Do not mix with other chemicals. Aerosol containers are unstable at temperatures above 49°C (120.2°F).
Incompatible materials	Acids. Oxidizing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.

11. Toxicological Information

Component analysis - LC50

Ingredient(s)	LC50
Butane	Not available
Ethylene glycol monobutyl ether	2.21 mg/l/4h rat
Pine oil	Not available
Propane	Not available

Component analysis - Oral LD50

Ingredient(s)	LD50
Butane	Not available
Ethylene glycol monobutyl ether	470 mg/kg rat; 320 mg/kg rabbit
Pine oil	3200 mg/kg rat
Propane	Not available

Effects of acute exposure

Eye	Causes chemical burns. May cause blindness.
Skin	May cause chemical burns. Harmful contact may not cause immediate pain. Contains a potential skin sensitizer. This product may be harmful if it is absorbed through the skin.

NIOSH - Pocket Guide - Skin Notations

Ethylene glycol monobutyl ether	111-76-2	Potential for dermal absorption
---------------------------------	----------	---------------------------------

Inhalation Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness).

Ingestion Not a normal route of exposure. May cause stomach distress, nausea or vomiting.

Sensitisation Non-hazardous by WHMIS criteria. Contains a potential skin sensitizer.

Local effects Toxic in contact with skin.

Chronic effects Non-hazardous by WHMIS criteria.

Carcinogenicity Non-hazardous by WHMIS criteria.

ACGIH - Threshold Limits Values - Carcinogens

Ethylene glycol monobutyl ether	111-76-2	A3 - Confirmed animal carcinogen with unknown relevance to humans.
---------------------------------	----------	--

IARC - Group 3 (Not Classifiable)

Ethylene glycol monobutyl ether	111-76-2	Monograph 88 [2006]
---------------------------------	----------	---------------------

Mutagenicity Non-hazardous by WHMIS criteria.

Reproductive effects Non-hazardous by WHMIS criteria.

Teratogenicity Non-hazardous by WHMIS criteria.

12. Ecological Information

Ecotoxicity effects Components of this product have been identified as having potential environmental concerns.

Ecotoxicity - Freshwater Fish Species Data

Ethylene glycol monobutyl ether	111-76-2	96 Hr LC50 Lepomis macrochirus: 1490 mg/L [static]
---------------------------------	----------	--

Ecotoxicity - Water Flea Data

Ethylene glycol monobutyl ether	111-76-2	24 Hr EC50 water flea: 1720 mg/L; 24 Hr LC50 Daphnia magna: 1698-1940 mg/L
---------------------------------	----------	--

Environmental effects Not available

Aquatic toxicity Not available

Persistence and degradability	Not available
Bioaccumulation/accumulation	Not available
Partition coefficient	Not available
Mobility in environmental media	Not available
Chemical fate information	Not available

13. Disposal Considerations

Waste codes	Not available
Disposal instructions	Dispose in accordance with all applicable regulations.
Waste from residues / unused products	Not available
Contaminated packaging	Not available

14. Transport Information

Transportation of Dangerous Goods (TDG)

Basic shipping requirements:

Proper shipping name	AEROSOLS, non-flammable, containing substances in Class 6.1, packing group III and in Class 8, packing group III
Hazard class	2.2 (6.1,8)
UN number	UN1950
Additional information:	
Special provisions	80
Packaging exceptions	<1L - Consumer Commodity



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Canada - WHMIS - Ingredient Disclosure List

Butane	106-97-8	1 %
Ethylene glycol monobutyl ether	111-76-2	1 %

WHMIS classification Class A - Compressed Gas, Class D - Division 1B, 2B, Class E - Corrosive Material
WHMIS status Controlled

WHMIS labeling



Inventory Status

Country(s) or region	Inventory Name	On Inventory (Yes/No)*
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

10-Dec-2007

Effective Date

31-Dec-2007

Expiry Date

31-Dec-2010

Prepared by

Dell Tech Laboratories Ltd. (519) 858-5021