


MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product Name 161 – YA002C ProLink Low VOC Apple Dry Air & Fabric Deodorizer
CAS # Mixture
Product Use Air freshener / Deodorizer
Manufacturer Pro-Link, Inc.
Ottawa, Ontario
K1Z 1E9 Canada
Phone: 1-800-74-LINKS
Emergency Phone: 1-866-836-8855

LEGEND HMIS/NFPA	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

Health	/ 1
Flammability	4
Physical Hazard	0
Personal Protection	B



2. Hazards Identification

Emergency Overview DANGER
Extremely flammable. Contents under pressure. Containers may explode when heated.
EYE AND SKIN IRRITANT.

Potential short term health effects

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Eyes May cause irritation.

Skin May cause irritation.

Inhalation Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness).

Ingestion Not a normal route of exposure. May cause stomach distress, nausea or vomiting.

Target organs Eyes. Respiratory system. Skin.

Chronic effects Prolonged or repeated exposure can cause drying, defatting and dermatitis.

Signs and symptoms Symptoms may include redness, oedema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

3. Composition/Information on Ingredients

Ingredient(s)	CAS #	Percent
Fragrance	Mixture	1 - 5
Propane	74-98-6	10 - 30
Butane	106-97-8	10 - 30
Acetone	67-64-1	60 - 100

4. First Aid Measures

First aid procedures

Eye contact Immediately flush with cool water. Remove contact lenses, if applicable, and continue flushing for 15 minutes. Obtain medical attention immediately.

Skin contact Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.

Inhalation If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. If breathing has stopped, trained personnel should administer CPR immediately.

Ingestion

Do not induce vomiting. Rinse mouth with water, then drink one or two glasses of water. Obtain medical attention. Never give anything by mouth if victim is unconscious, or is convulsing.

Notes to physician

Symptoms may be delayed.

General advice

Keep away from sources of ignition. No smoking. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting Measures

Flammable properties

Flammable aerosol by flame projection test. Containers may explode when heated.

Extinguishing media**Suitable extinguishing media**

Carbon dioxide. Alcohol foam. Dry chemical. Foam. Water Fog.

Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

Protection of firefighters**Specific hazards arising from the chemical**

Contents under pressure. Pressurized container may explode when exposed to heat or flame. Cool containers with flooding quantities of water until well after fire is out.

Protective equipment for firefighters

Firefighters should wear full protective clothing including self contained breathing apparatus.

Hazardous combustion products

May include and are not limited to: Oxides of carbon.

Explosion data**Sensitivity to mechanical impact**

Not available

Sensitivity to static discharge

Not available

6. Accidental Release Measures

Personal precautions

Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Before attempting clean up, refer to hazard data given above. Remove sources of ignition. Although the chance of a significant spill or leak is unlikely in aerosol containers, in the event of such an occurrence, absorb spilled material with a non-flammable absorbent such as sand or vermiculite.

7. Handling and Storage

Handling

Use good industrial hygiene practices in handling this material.

Storage

Keep out of reach of children. Do not store at temperatures above 49°C (120.2°F). Keep away from heat, open flames or other sources of ignition.

8. Exposure Controls / Personal Protection

Exposure limits

Ingredient(s)	Exposure limits
Acetone	ACGIH-TLV TWA: 500 ppm STEL: 750 ppm
Butane	ACGIH-TLV TWA: 1000 ppm
Fragrance	ACGIH-TLV Not established
Propane	ACGIH-TLV TWA: 1000 ppm

Engineering controls

General ventilation normally adequate.

Personal protective equipment

Eye/Face protection

Wear safety glasses with side shields.

Hand protection

Rubber gloves. Confirm with a reputable supplier first.

Skin and body protection

As required by employer code.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.

9. Physical & Chemical Properties

Appearance	Compressed liquefied gas
Colour	Clear, colourless to Light yellow
Form	Misty spray
Odour	Apple.
Odour threshold	Not available
Physical state	Gas
pH	Not available
Freezing point	Not available
Boiling point	13.00 °C (55.4 °F) (Estimated)
Flash point	< -17.77 °C (< 0 °F) (propellant)
Evaporation Rate	Not available
Flammability	32.53 kJ/g (Estimated)
Flammability limits in air, lower, % by volume	Not available
Flammability Limits in Air, Upper, % by Volume	Not available
Vapour pressure	467 kPa
Vapour density	Not available
Specific gravity	0.7945 (Concentrate)
Octanol/water coefficient	Not available
Solubility (H2O)	Complete
Auto-ignition temperature	Not available
VOC (Weight %)	Not available
Viscosity	Not available
Percent volatile	Not available

10. Chemical Stability & Reactivity Information

Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Aerosol containers are unstable at temperatures above 49°C (120.2°F). Do not mix with other chemicals.
Incompatible materials	Acids. Oxidizers. Caustics. Reducing agents.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.

11. Toxicological Information

Component analysis - LC50

Ingredient(s)	LC50
Acetone	> 16000 mg/m ³ rat
Butane	Not available
Fragrance	Not available
Propane	Not available

Component analysis - Oral LD50

Ingredient(s)	LD50
Acetone	5800 mg/kg rat
Butane	Not available
Fragrance	Not available
Propane	Not available

Effects of acute exposure

Eye	May cause irritation.
Skin	May cause irritation.
Inhalation	Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness).
Ingestion	Not a normal route of exposure. May cause stomach distress, nausea or vomiting.
Sensitisation	Non-hazardous by WHMIS criteria.
Chronic effects	Non-hazardous by WHMIS criteria.
Carcinogenicity	Non-hazardous by WHMIS criteria.

ACGIH - Threshold Limits Values - Carcinogens

Acetone	67-64-1	A4 - Not Classifiable as a Human Carcinogen
---------	---------	---

Mutagenicity Non-hazardous by WHMIS criteria.

Reproductive effects Non-hazardous by WHMIS criteria.

Teratogenicity Non-hazardous by WHMIS criteria.

12. Ecological Information

Ecotoxicity effects Components of this product have been identified as having potential environmental concerns.

Ecotoxicity - Freshwater Fish Species Data

Acetone	67-64-1	96 Hr LC50 Oncorhynchus mykiss: 5540 mg/L [static]; 96 Hr LC50 Pimephales promelas: 6210 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 8300 mg/L [static]
---------	---------	--

Ecotoxicity - Microtox Data

Acetone	67-64-1	15 min EC50 Photobacterium phosphoreum: 14500 mg/L
---------	---------	--

Ecotoxicity - Water Flea Data

Acetone	67-64-1	48 Hr EC50 water flea: 0.0039 mg/L; 48 Hr EC50 water flea: 12700 mg/L [Static]; 48 Hr EC50 Daphnia magna: 12600 mg/L
---------	---------	--

Environmental effects Not available

Aquatic toxicity Not available

Persistence and degradability Not available

Bioaccumulation/accumulation Not available

Partition coefficient Not available

Mobility in environmental media Not available
Chemical fate information Not available

13. Disposal Considerations

Waste codes Not available
Disposal instructions Dispose in accordance with all applicable regulations.
Waste from residues / unused products Not available
Contaminated packaging Not available

14. Transport Information

Transportation of Dangerous Goods (TDG)

Basic shipping requirements:

Proper shipping name Aerosols, flammable
Hazard class 2.1
UN number 1950
Additional information:
Special provisions 80
Packaging exceptions <1L - Consumer Commodity



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Canada - WHMIS - Ingredient Disclosure List

Acetone	67-64-1	1 %
Butane	106-97-8	1 %

WHMIS classification Class A - Compressed Gas, Class B - Division 5; Flammable Aerosol, Class D - Division 2B

WHMIS status Controlled

WHMIS labeling



Inventory Status

Country(s) or region	Inventory Name	On Inventory (Yes/No)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date	11-Dec-2007
Effective Date	01-Jan-2008
Expiry Date	01-Jan-2011
Prepared by	Dell Tech Laboratories Ltd. (519) 858-5021